BRYANT®

Locking Devices, Elastomeric, Male Plug, 20A125/250V, 3-Pole 4-Wire Grounding, L14-20P, Screw Terminal, Yellow, Water/Dust-Tight Housing

By Bryant
Catalog # BRY26W74



Watertight Devices, Locking Devices, Elastomeric, Male Plug, 20A 125/250V, 3-Pole 4-Wire Grounding, L14-20P, Screw Terminal, Yellow ,Water/Dust-Tight Housing

Features

- Triple bypass seal keeps water away from electrical connections and works with previously installed devices
- Corrosion-resistant connection points
- High conductivity brass termination
- Cone seal accomodates any cable range
- Keyed interior for easy installation

General

Color	Yellow
Item Type	20A Watertight Plug
Number Of Poles	3-Pole
Performance	• Dielectric voltage:2000V AC if rated 300V or less, 3000V AC if rated above 300V • Moisture resistance:UL Listed to 3R, 3RX, 4, 4X, 6, 6P, 12 • UV resistance:All exposed materials are UV stabilized • Flammability:UL94V2 (plugs, connectors, and interiors)
Type	Plugs
UPC	781786378407

Dimensions

Dimensions	2.51 in x 2.51 in x 3.96 in
Height	3.96 in
Length	2.51 in
Width	2.51 in

Electrical Ratings

Amperage Rating	20 A
Voltage Rating	125/250 VAC
Voltage Rating Description	125/250 VAC

Conductor Related

Number Of Wires	4-Wire
Wire Size	Min. cord: #16/3 SJ, #18/3 S, #18/4 SJ, #18/4 S, #18/5 S;Max. cord: #10/3 S, #10/4 S, #10/5 S

Certifications and Compliance

Industry Standard(s)	• IP69K • Listed to UL498 • Certified to CSA C22.2 No. 42 • Meets NEMA® WD-1, WD-6, and ANSI Standards • IP66 Suitability • NSF Certified (plugs, connectors and receptacles)
Nema Rating	L14-20P

Logistics

Carton Quantity	10

Product Assets

Catalog Page - Bryant I-6 Catalog page
Catalogs - Bryant Full Line Catalog
Literature - General Literature - Watertight Wiring Devices

Related Products

BRYWTB2 - Watertight Replacement Bushing Set, Size 2
BRYWTCS2 - Watertight Replacement Cone Seal, Size 2
BRY67W74 - Watertight Series, Locking Receptacle, 20A 125/250V AC, 3-Pole 4-Wire Grounding, NEMA L14-20R, Yellow
BRY27W74 - Locking Devices, Elastomeric, Male Plug, 20A 125/250V, 3-Pole 4-Wire Grounding, L14-20R, Screw Terminal, Yellow Water/Dust Tight Housing

©2023 Hubbell Incorporated. All rights reserved.
BRY-BRY26W74-SPEC-EN | REV 5/2023