



STACKING ADAPTER

By Burndy
Catalog # [CUSA442NTC](#)

Copper, tin plated, 2 hole (1/2" stud - 1-3/4" hole spacing), up to 35kV, used to elevate terminals for vertical parallel conductor accommodates. Adapter length 3.00", width 1.12", height 1.50



Application

Stacking Adapter

General

Connector Type	STACKING ADAPTER
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Physical Attribute - Number of Holes	2
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	STACKING ADAPTERS
Temperature Rating	194
Trade Name	HYSTACK™
Type	Standard Barrel, Tin Plated
UPC	781810269176
UPC 12 Digit	7818102691766

Dimensions

Dimension - Bolt Size fraction	1/2
Dimension - Height inch	1.50 in
Dimension - Hole Size fraction	1/2
Dimension - L Length Overall mm	76 mm
Dimension - Length Overall inch	3.00 in
Dimension - Stud Size fraction	1/2
Dimension - Stud Size inch	1/2
Dimension - Width inch	1.13 in
Dimension - Width mm	29 mm
Physical Attribute - Tongue Angle	Straight

Electrical Ratings

Voltage - Maximum	35000
-------------------	-------

Conductor Related

Conductor - AL Str Size	1000 KCMIL
Conductor - Copper Str Compact Size	1000 KCMIL
Conductor - Copper Str Size	1000 KCMIL
Conductor - Copper Str Size Range	10 AWG - 750 kcmil
Conductor - Material	COPPER
Conductor Type	CODE/FLEX
Wire Size	1000 KCMIL

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Carton Quantity	1
Minimum Pack Quantity	1

Product Assets

- [3D Models - CUSA442NTC_MODEL-IGES](#)
- [3D Models - CUSA442NTC_MODEL-STEP](#)
- [3D Models - CUSA442NTC_MODEL-PDF](#)
- [Catalogs - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Sales Drawings - SC212660-01](#)



A proud member of the Hubbell Family.

