



Compression Terminal

By Burndy
Catalog # [YAV26L2TC14FX](#)

2/0 Flex G,H,I,K,M,DLO, 2/0 AWG CU, Two Hole, 1/4 Stud Size, 5/8 Hole Spacing, Standard Barrel, Inspection Window, Internal Chamfer, Tin Plated, UL/CSA, 90°C, Up to 35kV, Black Color Code, 13 Die Index.



Application

Wire Termination

General

| | |
|--------------------------------------|---|
| Color Code | Black |
| Connector Type | STANDARD BARREL |
| Die Index | 13 |
| EU RoHS Indicator | Yes |
| Feature - Barrel Style | <ul style="list-style-type: none"> • Chamfered • Skived |
| Feature - Barrel Type | Standard |
| Finish Type | Tin-Plated |
| Material | COPPER |
| Physical Attribute - Number of Holes | 2 |
| Plated | Y |
| Plating Type | Tin |
| Sub Brand | HYLUG |
| Temperature Rating | 194 |
| Trade Name | HYLUG™ |
| Type | Standard Barrel, Tin Plated |
| UPC | 781810035733 |
| UPC 12 Digit | 7818100357333 |

Dimensions

| | |
|-----------------------------------|----------|
| Dimension - B Length fraction | 13/16 in |
| Dimension - B Length inch | 0.81 in |
| Dimension - Bolt Hole Size inch | 0.27 in |
| Dimension - Bolt Size fraction | 1/4 |
| Dimension - Bolt Size inch | 0.25 |
| Dimension - Hole Size fraction | 1/4 |
| Dimension - Hole Size inch | 0.27 |
| Dimension - Hole Size mm | 6.9 mm |
| Dimension - L Length Overall mm | 65 mm |
| Dimension - Length Overall inch | 2.56 in |
| Dimension - N inch | 0.31 in |
| Dimension - Outside Diameter inch | 0.63 in |
| Dimension - Pad Width inch | 0.93 in |
| Dimension - Strip Length inch | 13/16 in |
| Dimension - Stud Size fraction | 1/4 |
| Dimension - Z inch | 0.34 in |

Conductor Related

| | |
|--|---------------|
| Conductor - Copper DLO Size | 2/0 AWG |
| Conductor - Copper DLO Size Range | 2/0 AWG |
| Conductor - Copper Flex G Size | "2/0 AWG" |
| Conductor - Copper Flex G Size Range | 2/0 AWG |
| Conductor - Copper Flex H Size | "2/0 AWG" |
| Conductor - Copper Flex H Size Range | 2/0 AWG |
| Conductor - Copper Flex I Size | "2/0 AWG" |
| Conductor - Copper Flex I Size Range | 2/0 AWG |
| Conductor - Copper Flex K Size | "2/0 AWG" |
| Conductor - Copper Flex K Size Range | 2/0 AWG |
| Conductor - Copper Flex M Size | "2/0 AWG" |
| Conductor - Copper Flex M Size Range | 2/0 AWG |
| Conductor - Copper Solid Size | 2/0 AWG |
| Conductor - Copper Solid Size Range | 2/0 AWG |
| Conductor - Copper Str Compact Size | "2/0 AWG" |
| Conductor - Copper Str Navy Size | 125 |
| Conductor - Copper Str Navy Size Range | 125 (61) Navy |
| Conductor - Copper Str Size | "2/0 AWG" |
| Conductor - Copper Str Size Range | 2/0 AWG |
| Conductor - CopperWeld Str Size | 2/0 WELD |
| Conductor - CopperWeld Str Size Range | 2/0 WELD |
| Conductor - Material | COPPER |
| Conductor Size | 2/0 AWG |
| Conductor Type | CODE/FLEX |
| Wire Size | 2/0 AWG |

Certifications and Compliance

| | |
|------------------------------|-----|
| Certification - CSA Approved | Yes |
| Certification - ETL | No |

Dimension - Z Inch 0.34 in
Physical Attribute - Tongue Angle Straight

Electrical Ratings

Voltage - Maximum 35000
Voltage Rating 35 kV

Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL 486A-486B
Standards - RoHS Compliance Status CM
UL Listed Yes

Logistics

Carton Quantity 50
Minimum Pack Quantity 1
Pallet Quantity 23200

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Installation Manuals - Copper Flex Standard Terminals Tooling and Installation Instructions](#)
[Sales Drawings - SE..208119-01](#)
[Video - HYDENT Compression Terminal Overview Video](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
BRDY-YAV26L2TC14FX-SPEC-EN | REV 6/2023