

PVC COATED DEVICE BOXES - FSC

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 1"
- Sealing sleeves on all conduit openings
- Modified boxes are available upon request
- All available covers are supplied with PVC coating

Applications:

Allied Tube & Conduit® Type FSC PVC Coated Device Boxes offer corrosion protection to conduit systems and accommodates wiring devices and access for taps and splices. Covers are available separately. Electrical continuity of the conduit system is maintained across assembled system.



Standards:

- UL Listed Standard 514B File #E307133
- CSA Standard: C22.2 No. 18

Part Number	Trade Size (in)	Weight per 100 (lbs)	A (in)	B (in)	C (in)	D (in)	Aluminum Item Number
Single Gang							
PV0500FSC1	½	2.20	1.380	1.920	1.690	0.670	PA0500FSC1SA
PV0700FSC2	¾	2.40	1.630	1.920	1.690	0.790	PA0700FSC2SA
PV1000FSC3	1	2.70	2.000	1.920	1.690	0.920	
Double Gang							
PV0500FSC12	½	3.30	1.380	1.920	1.690	0.670	
PV0700FSC222	¾	3.60	1.630	1.920	1.690	0.790	
PV1000FSC32	1	4.00	2.000	1.920	1.690	0.920	

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit alliedeg.us