

PVC COATED GUA JUNCTION BOXES FOR HAZARDOUS LOCATIONS - GUAT

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 2"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes ½"- 2"

Applications:

Allied Tube & Conduit® GUA Style Fittings are available in a variety of shapes and dimensions. GUA style boxes are used in hazardous locations. All GUA style boxes are supplied PVC coated with PVC coated covers and a seal between the coating of the boxes and the coating of the covers.



Standards:

- National Electric Code:
Class I, Division 1 & 2, Groups C, D, Class III
- UL Standard 886
- ANSI Standard C-33.27
- CSA Standard: C22.2 No. 30
- NEMA/EEMAC 3, 4

| Part Number | Trade Size (in) | Cover Opening (in) | A (in) | B (in) | C (in) | D (in) | Weight per 100 (lbs) |
|--------------|-----------------|--------------------|--------|--------|--------|--------|----------------------|
| PV0500GUAT14 | ½ | 2 | 2.58 | 2.29 | 2.19 | 0.67 | 200 |
| PV0500GUAT16 | ½ | 3 | 3.58 | 2.04 | 1.88 | 0.67 | 280 |
| PV0700GUAT24 | ¾ | 2 | 2.58 | 2.04 | 2.00 | 0.79 | 220 |
| PV0700GUAT26 | ¾ | 3 | 3.58 | 2.04 | 1.88 | 0.79 | 350 |
| PV1000GUAT36 | 1 | 3 | 3.58 | 2.35 | 2.19 | 0.92 | 320 |
| PV1200GUAT47 | 1¼ | 3½ | 4.33 | 2.73 | 2.75 | 1.13 | 570 |
| PV1500GUAT59 | 1½ | 5 | 5.83 | 3.85 | 3.75 | 1.32 | 910 |
| PV2000GUAT69 | 2 | 5 | 5.83 | 4.10 | 4.00 | 1.60 | 1000 |

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit alliedeg.us