

# **BIBD43, Double Sided Three Conductor Clear Insulated Mult-Tap Connector**

By Burndy Catalog # BIBD43

Aluminum Multiple Tap Connector, Clear Insulated, 3 Port, 2 Sided Entry, 14-4 AWG, AI/Cu Rated.



#### **Application**

For Indoor Use Only, Copper Or Stranded Aluminum

#### General

Connector Type Multi Tap **EU RoHS Indicator** Yes 1/8 Hex Key Insulation Insulation Type Plastisol Material Aluminum Material - Hardware Aluminum

Number Of Ports Physical Attribute - Number of 3

Screws

Physical Attribute - Screw Allen

Type

Plated Plating Type Unplated Sub Brand UNITAP Temperature Rating UNITAP™ Trade Name Type BIBD. Multi-Port UPC 781810223857

Ν

7818102238577

## UPC 12 Digit **Dimensions**

Dimension - Height fraction 1.25 in Dimension - Height inch 1.25 in Dimension - L Length Overall 38 mm mm Dimension - Length Overall 1.51 in

Dimension - Screw Size inch 1/4 Dimension - Width fraction 1-1/2 in Dimension - Width inch 1.50 in Dimension - Width mm 38 mm

#### **Electrical Ratings**

600 V Voltage - Maximum

#### **Conductor Related**

Conductor - AL Str Size 8 AWG;6 AWG;4 AWG Conductor - AL Str Size 8 AWG-4 AWG

Range

14 AWG:12 AWG:10 AWG:9 Conductor - Copper Str Size

AWG;8 AWG;7 AWG;6 AWG;5

AWG:4 Str 14 AWG - 4 AWG

Conductor - Copper Str Size

Range

Conductor Size 14-4 AWG

Conductor Type • AL C Str-Size

• CU C Str-Size

#### **Certifications and Compliance**

Certification - CSA Approved Certification - ETL Nο Certification - UL Listed Direct No Burial

Certification - UL Recognized Certification - cULus

Industry Standard(s) UL 486A-486B Standards - Industry UL 486A-486B

Standards Met

Standards - RoHS Compliance СМ

Status

**UL** Listed Yes

### Logistics

Minimum Pack Quantity

#### **Product Assets**

3D Models - BIBD43 MODEL-STEP 3D Models - BIBD43 MODEL-IGES 3D Models - BIBD43\_MODEL-PDF Catalogs - UNITAP™ Products Catalogs - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice Sales Drawings - sc210991-04

