



PENA134, Oxide Inhibitor, 4 ounce

By Burndy
Catalog # [PENA134](#)

Oxide Inhibiting Electrical Joint Compound, 4 OZ, For Al-Al, Al-Cu & Al Conduit Threads / Insulated Cable.



Application

Aluminum to Aluminum, Aluminum to Conduit, Aluminum to Copper

General

Application - For Use On	Aluminum to Aluminum;Aluminum to Conduit;Aluminum to Copper
Container Type	Squeeze Bottle
EU RoHS Indicator	Yes
Pour Point	-40 °F
Sub Brand	PENETROX
Temperature - Dropping Point Fahrenheit	350 °F
Trade Name	PENETROX™
Type	Sealing compound
UPC	781810593127
UPC 12 Digit	7818105931277
Viscosity at 100 Fahrenheit	250 °F

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Container Size	4 oz
Minimum Pack Quantity	1

Product Assets

- [3D Models - PENA134_MODEL-STEP](#)
- [3D Models - PENA134_MODEL-IGES](#)
- [3D Models - PENA134_MODEL-PDF](#)
- [Catalogs - Full Line BURNDY Catalog](#)
- [Sales Drawings - sc087704-01](#)
- [SDS - PENETROX_A-13_GHS](#)
- [SDS - PENETROX_A-13_GERMAN_GHS](#)
- [SDS - PENETROX_A-13_PORTUGUESE_GHS](#)
- [SDS - PENETROX_A-13_ESPANOL_GHS](#)
- [SDS - PENETROX_A-13_FRENCH_GHS](#)
- [SDS - PENETROX_A-13_ITALIAN_GHS](#)



A proud member of the Hubbell Family.