

# KLU125, Copper Terminal, Offset Tongue, 1 Hole, 2-1/0 AWG (Str), 1/4" Stud, 1 Screw

By Burndy Catalog # KLU125

Copper Terminal, Offset Tongue, 1 Hole, 2-1/0 AWG (Str), 1/4" Stud, 1 Screw.



### **Application**

For Joining A Wide Range Of Copper Cable To Equipment Pads Or Bar

#### General

Connector Type Pressure Bar

**EU RoHS Indicator** 

3/8 UNF Slotted SetScrew Hardware Type

Installation Torque 50

Recommended in-lb

Material Copper

Physical Attribute - Number of 1

Holes

Physical Attribute - Number of 1

Screws

Physical Attribute - Screw Slot

Type

Plated Ν Plating Type

Unplated Sub Brand **SCRULUG** Trade Name SCRULUG™

Type **Bolted Lugs & Terminals** 

UPC 781810351390

#### **Dimensions**

Dimension - B Length fraction 5/8 in Dimension - B Length inch 0.61 in Dimension - Bolt Size fraction Dimension - Hole Size inch 0.26 in Dimension - Hole Size mm 7 mm Dimension - L Length Overall 50 mm

mm

Dimension - Length Overall

inch

Dimension - N inch 0.42 in Dimension - Pad Width inch 0.62 Dimension - Screw Size inch 3/8

Dimension - Strip Length inch 15/16 Dimension - Stud Size inch 1/4

## **Conductor Related**

Conductor - Copper Str Size 2 AWG;1 AWG;1/0

Conductor - Copper Str Size 2 AWG-1/0

Range

Conductor Size 2-1/0 AWG CU C Str-Size Conductor Type

## **Certifications and Compliance**

Certification - CSA Approved Certification - ETL Certification - UL Listed Direct No

Burial

Certification - UL Recognized Certification - cULus Yes Industry Standard(s) **UL467** Standards - Industry **UL467** 

Standards Met

Standards - RoHS Compliance

Status

**UL** Listed No

#### Logistics

Minimum Pack Quantity

# **Product Assets**

Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - sd207469-01



1.98 in