



BIBS5004DB, Direct Burial Submersible Four Conductor Insulated Multi-Tap Connector

By Burndy
Catalog # BIBS5004DB



Multi Port Direct Burial, 4 Ports, 500 kcmil-12 AWG Str, 600 V.

Application

For Outside Direct Burial

General

Connector Type	Multi Tap
EU RoHS Indicator	Yes
Installation Torque Recommended in-lb	550 LBS/in
Insulation	Y
Material	Aluminum
Number Of Ports	4
Plated	N
Plating Type	Unplated
Sub Brand	UNITAP
Temperature Rating	194
Trade Name	UNITAP™
Type	BIBS, Multi-Port - Direct Burial
UPC	781810523643
UPC 12 Digit	7818105236433

Dimensions

Dimension - Height inch	3.13 in
Dimension - L Length Overall mm	145 mm
Dimension - Length Overall inch	5.69 in
Dimension - Strip Length inch	1.50
Dimension - Width inch	4.58 in
Dimension - Width mm	116 mm

Electrical Ratings

Operating Voltage	600 V
Voltage - Maximum	600 V

Conductor Related

Conductor - AL Str Size Range	12 - 500 Str
Conductor - Copper Str Size Range	12 AWG - 500 kcmil
Conductor Size	12 AWG-500 KCMIL
Conductor Type	<ul style="list-style-type: none">• AL C Str-Size• CU C Str-Size

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Listed Direct Burial	Yes
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[Catalogs - UNITAP™ Products](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - 30013660](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
BRDY-BIBS5004DB-SPEC-EN | REV 8/2023