



YCAK33R4N

By Burndy
Catalog # YCAK33R4N



Al Compression terminal, 336.4 Kcmil ACSR(26-7, 30-7) str
397.5 Kcmil Al(19)Str, .56"stud, 7.34"L, , 316 index.

Application

For ACSR/6201/5005 (Compressed/Compact), Aluminum

General

Die Index	316
EU RoHS Indicator	Yes
Material	Aluminum
Physical Attribute - Pad Configuration	4 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	TERMINALS
Trade Name	HYLUG™
Type	YCAK-R-N, Terminal
UPC	781810810231
UPC 12 Digit	7818108102311

Dimensions

Dimension - B Length inch	3.05 in
Dimension - Bolt Hole Size inch	0.56 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	187 mm
Dimension - Length Overall inch	7.34 in
Dimension - Pad Width inch	3 in

Conductor Related

Conductor - ACSR Str Size	336.4 (26-7) kcmil;336.4 (30-7) kcmil
Conductor - ACSR Str Size Range	336.4 (26-7) kcmil;336.4 (30-7) kcmil
Conductor - AL Str Size	397.5 kcmil
Conductor - AL Str Size Range	397.5 kcmil

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	10
-----------------------	----

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - SD..029515-01](#)



A proud member of the Hubbell Family.