

Tee, Aluminum Compression

By ANDERSON
Catalog # [ORT2115](#)

"Tee-Taps,Aluminum Compression,Open Run Cable to Cable,
For ACSR,AAC,AAAC,ACAR, 1.140" - 1.235" Main to Tap 1.140" -
1.235""



*Representative Image

Features

- "To have the pad rotated 90 degrees, add '90' to The end of the catalog ex: ORT211590
- Tees are EHV rated where conductor dia. is 1" or larger"

General

EU RoHS Indicator	No
Material	Aluminum
Number of Ground Braid Lug Holes	0
Number of Pad Holes	4
Type	Tee, Aluminum Compression
UPC	096359366126

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Run Length before Compression	22 in
Weight	6.860 lb
Width - Flat Bar Tap	3 in

Electrical Ratings

Maximum Current Rating Amps Continuous	0
---	---

Conductor Related

Conductor Compatibility	ACSR-Grackle-1192.5-54/19;ACSR-Bittern-1272-45/7;ACSR-Pheasant-1272-54/19;ACSR-Dipper-1351.5-45/7;AAC-Columbine-1351.5-61;AAC-Carnation-1431-61;AAC-Gladiolus-1510.5-61
Conductor Diameter (Main) - Maximum	1.425 in
Conductor Diameter (Main) - Minimum	1.331 in
Conductor Diameter (Main) Range	1.331 - 1.425
Conductor Type	• AAC • ACSR

Logistics

Pallet Quantity	120
-----------------	-----

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)
[Sales Drawings - CC-21493 \(ORT21 Product Family\)](#)

