

Compression TerminalStraight,
Partial Tension

By ANDERSON
Catalog # [JTS11](#)



*Representative Image

Features

- "Jumper terminals are prefilled with inhibitor
- Standard hardware includes Aluminum 1/2-13 bolt, nut and two aluminum washers
- Add "SS" suffix to specify stainless steel hardware
- Jumper terminals for conductors 1.00 inch diameter or larger are EHV rated
- Die Size: 11CD
- Minimum Press Tons: 60"

General

Bolt Installation Torque (Recommended)	0 ft-lbs
Compression Method	Uni-Grip (single die system)
Die Size	10CD
EU RoHS Indicator	No
Material & Connection Method	Aluminum Compression
Number of Bolt Holes	0
Number of Pad Holes	2
Number of Tees	0
Press Minimum	60 to
Product Category	Compression Jumper Terminal
Tension Range	0 lb
UPC	096359404934

Dimensions

Angle - Pad	0 °
Assembly Rating (Ultimate)	0 lb
Diameter - Bolt	0 in
Diameter - Outside	0 in
Diameter - Pad Bolt	0 in
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	11.4 in
Messenger Diameter Range	0 - 0
Nominal Guy Wire Size	0 in
Thickness - Pad	0 in
Weight	1.960 lb
Width - Pad	2.2 in

Electrical Ratings

Voltage Application	Standard
---------------------	----------

Conductor Related

Conductor Compatibility	ACSR-Eagle-556.5-30/7;ACSR-Peacock-605-24/7;ACSR-Squab-605-26/7;ACSR-Rook-636-24/7;ACSR-Grosbeak-636-26/7;ACSR-Gannet-666.6-26/7;ACSR-Stilt-715.5-24/7;AAC-Flag-700-61;AAC-Cattail-750-61;AAC-Arbutus-795-37;AAC-Lilac-795-61
Conductor Diameter (Main) - Maximum	0 in
Conductor Diameter (Main) - Minimum	0 in
Conductor Diameter (Main) Range	0 - 0
Conductor Diameter - Maximum	0 in
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

Product Assets

[Catalogs - Transmission Connectors Catalog - Full \(CA05063E\)](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
AN-JTS11-SPEC-EN | REV 9/2023