

Stud Connector, Bronze

By ANDERSON
Catalog # [DS2020012](#)

"Bolted Stud Connectors, Connecting Stud to Cable, Stud Dia./Thd.-1-1/2"-12, Copper Conductor Range- Cable- 1/0-Sol.-500-MCM,Dia-0.325"-0.813", Material: Castings-Bronze Alloy, Hardware-Silicon Bronze or Stainless Steel"



*Representative Image

Features

- 0

General

EU RoHS Indicator	No
Material	Bronze
Material - Clamping Hardware	Stainless Steel
Number of Ground Braid Lug Holes	0
Number of Stud Threads	12
Type	Studs
UPC	096359300373

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Diameter - Stud	2 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	9.310 lb

Electrical Ratings

Maximum Current Rating	0
Amps Continuous	

Conductor Related

Conductor Diameter - Maximum	1.632 in
Conductor Diameter - Minimum	0.46 in
Conductor Diameter Range	0.46 - 1.632
Conductor Type	Copper

Product Assets

[Catalogs - Substation Connectors \(SA\)](#)
[Sales Drawings - CC-1487 \(DS Product Family\)](#)
[Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products \(VI05050E0619\)](#)
[Video - Hubbell Power Systems Quick Ship \(VI05124E1018\)](#)

