

Suspension Clamp

By ANDERSON
Catalog # [HAS227S](#)

"The HAST2 suspension clamp is a double groove, saddle type suspension clamp designed for use on standard voltage T2 transmission lines. Type HAST2 is recommended for AAC, ACSR, or AAAC T2 conductors. Maximum conductor temperature 130°C. Material: Clamp-Aluminum alloy, Socket-Galvanized Ductile iron. Clamping Range: 0.684"-0.814"



*Representative Image

Features

- "Bolt and nut may be substituted for clevis pin by adding suffix "BNK" to catalog number
- The clevis bolt and clevis pin are the same diameter
- "S" suffix indicates the suspension clamp will contain the socket eye SA22"

General

Bolt Installation Torque (Recommended)	720 in-lbs
EU RoHS Indicator	No
Fitting Type	Socket
Material - Clamp	Aluminum
Material - Hardware	Galvanized Steel
Material - Pin (Cotter)	Stainless Steel
Material - Socket and Clevis	Galvanized Ductile Iron
Product Category	Suspension Clamp
Strength Rating - Ultimate Body	30000 lb
Type	Standard Voltage Suspension Clamps
U-Bolts	5/8 in (15.9mm)
UPC	096359315087

Dimensions

Angle - Take-Off Maximum	17.5 °
Clamping - Maximum	2.27 in
Clamping - Minimum	1.75 in
Clevis Opening	2.41 in
Diameter - Clevis Pin	0.625 in
Height	3.88 in
Length	11 in
Weight	11.5 lb

Electrical Ratings

Voltage Application	Standard
---------------------	----------

Conductor Related

Clamping Range	1.75- 2.27
----------------	------------

Logistics

Pallet Quantity	72
-----------------	----

Product Assets

[Catalogs - Transmission Connectors Catalog - Full \(CA05063E\)](#)
[Literature - Ropes Course Industry Letter \(April 2021\)](#)

