HUBBELL
Power Systems, Inc.

Tee, Bronze Bolted

By ANDERSON
Catalog # T2CC100100

"Bolted Tees, Connecting Cable Main to Cable Tap, Cable Main- 4/0 Str.- 1000 MCM, Dia.- 0.460" -1.152", Cable Tap- # 4 Sol.-250 MCM, Dia.- 0.204"-0.575", Material: Castings- Bronze Alloy, Hardware-Silicon Bronze or Stainless Steel"



*Representative Image

Features

- "Tee for Connecting Copper Cable Main to Copper Cable Tap
- All sizes furnished with reversible cable caps"

General

EU RoHS Indicator	No
Material	Bronze
Material - Clamping Hardware	Stainless Steel
Number of Ground Braid Lug Holes	0
Type	Tee, Bolted
UPC	096359328834

Dimensions

Base Hole Spacing	0 in
Diameter - Base Holes	0 in
Diameter - Bolt	0 in
Diameter - Inside	0 in
Length - Coupling	0 in
Length Before Compression	0 in
Weight	7.546 lb

Electrical Ratings

Maximum Current Rating Amps Continuous	0

Conductor Related

Conductor Diameter (Main) - Maximum	1.152 in
Conductor Diameter (Main) - Minimum	0.46 in
Conductor Diameter (Main) Range	0.46 - 1.152
Conductor Diameter (Tap) - Maximum	1.152 in
Conductor Diameter (Tap) - Minimum	0.46 in
Conductor Diameter - Maximum	1.152 in
Conductor Diameter - Minimum	0.46 in
Conductor Diameter Range	0.46 - 1.152
Conductor Type	Copper

Product Assets

Catalogs - Substation Connectors (SA)
Sales Drawings - C-4157-2
Sales Drawings - C-4157-1
Video - Hubbell Power Systems 3D Portal to help with developing 3D models of substation connector products (VI05050E0619)
Video - Hubbell Power Systems Quick Ship (VI05124E1018)

©2023 Hubbell Incorporated. All rights reserved.