SIEMENS

Data sheet

3UF7941-0AA00-0

USB PC cable for connection to the USB interface of a PC length 2.5 m, for communication with SIMOCODE pro or SIRIUS 3RW44 soft starter or safety system 3SK2 and 3RK3 via the system interface



General technical data					
product brand name			SIRIUS		
product designation			USB PC cable		
ambient temperature					
 during storage 			-40 +80 °C		
during operation			-25 +60 °C		
 during transport 			-40 +80 °C		
Certificates/ approvals					
General Product App	roval	EMC	Test Certificates	Marine / Shipping	
<u>Confirmation</u>	EHC	RCM	Type Test Certific- ates/Test Report	ABS	KARS RARES
Marine / Shipping	other				
DNV-GL	<u>Confirmation</u>	Profibus			
https://press.siemens.c Siemens is working o Please contact your loc EAC relevant market (c Information on the pa https://support.industry	other than the sanctioned	se/siemens-wind-dowr rrent EAC certificate status of validity of the I EAEU member states view/109813875	s. e EAC certification if you inten	d to import or offer to supply	these products to an
https://www.siemens.co	om/ic10	5.0010163, <i>j</i>			

Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7941-0AA00-0

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7941-0AA00-0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3UF7941-0AA00-0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7941-0AA00-0&lang=en



C