



CORD SEALS

Watertight Cord Entrance Seal

HIGHLIGHTS

- Constructed of brass with neoprene grommet
- Cord seals are for use in underwater junction boxes as fixture cord entrance seals with type ST & SO water resistant cord



Specifications

Model	Cord Size	NPT	A	B
CS14302	18-3	1/2"	7/8"	1- 1/2"
CS14303	14-3	3/4"	1 -1/4"	1- 3/4"
CS14304	18-3	3/4"	1- 1/4"	1- 3/4"
CS143022	16-3	1/2"	7/8"	1- 1/2"
CS143032	12-3	3/4"	1- 1/4"	1- 3/4"
CS143033	10-3	3/4"	1- 1/4"	1- 3/4"

ORDERING INFORMATION

EXAMPLE: CS14302

Model	
CS14302	18-3 Cord Size, 1/2"NPT
CS14303	14-3 Cord Size, 3/4"NPT
CS14304	18-3 Cord Size, 3/4"NPT
CS143022	16-3 Cord Size, 1/2"NPT
CS143032	12-3 Cord Size, 3/4"NPT
CS143033	10-3 Cord Size, 3/4"NPT

Note: Hydrel Reserves The Right To Modify Specification Without Notice. Any dimension on this sheet is to be assumed as a reference dimension: "Used for information purposes only. It does not govern manufacturing or inspection requirements." (ANSI Y14.5-1973)

SPECIFICATIONS AND FEATURES

BODY AND NUT: Brass

GROMMET: Neaprene

BUY AMERICAN ACT: This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS and DOT regulations. Please refer to www.acuitybrands.com/resources/buy-american for additional information.

WARRANTY: 1-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/support/customer-support/terms-and-conditions

Consult factory for details.

NOTE: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.