Product specifications

Eaton DCU1104FRM

Catalog Number: DCU1104FRM

Eaton Heavy duty DC disconnect, 200 A, NEMA 3R, Stainless steel, Fusible, LC: In 300 MCM-#6 out 300 MCM-#6. SR: in 300 MCM-#6 out 300 MCM-#6. EG: in #4-#14 AWG out 1/0-#14, Max:1000 Vdc, NEMA 3R, 1, Fusible, System:1000 Vdc



General specifications

Product Name
Eaton heavy duty DC disconnect

Catalog Number
DCU1104FRM

UPC
786685625669

Product Length/Depth
11.63 in

Product Height
35.38 in

Product Width
16.54 in

Product Weight
45 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications
UL 98B
NEC 690 per UL 1741

Powering Business Worldwide

Product specifications

Maximum voltage
1000 VDC

Switch type
Heavy duty

Fuse configuration
Fusible

Enclosure
NEMA 3R

Amperage Rating
200 A

Enclosure material
Painted galvanized steel

Series
DC photovoltaic applications

Type
DC disconnect/ungrounded system

System voltage
1000 VDC

NEMA rating
NEMA 3R

Main lug wire size
LC: In 300 kcmil-#6 out 300 kcmil-#6. SR: in 300 kcmil-#6 out 300 kcmil-#6. EG: in #4-#14 AWG out 1/0-#14

Number of circuits
1

Voltage rating
1000 VDC

Protection
Fusible

Application
Solar

Resources

Brochures
DC disconnects for grounded and ungrounded photovoltaic installations

Multimedia
Double Up on Safety

Switching Devices Flex Center

Specifications and datasheets
Eaton Specification Sheet - DCU1104FRM



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia