

# Eaton 10316H700

Catalog Number: 10316H700

Eaton 10316 hazardous location limit switch, Non Plug-in Style Assembled Limit Switch, Top Rotary, Die Cast Zinc enclosure, 10A max AC, 0.22A max DC, 1NO-1NC, 10A at 600Vac, 0.22A at 125Vdc, Screw Terminals, Clockwise

## General specifications



### Product Name

Eaton 10316 hazardous location limit switch

### Catalog Number

10316H700

### UPC

782113229980

### Product Length/Depth

1.55 in

### Product Height

4.84 in

### Product Width

1.78 in

### Product Weight

1.125 lb

### Warranty

1 year

### Compliances

CE Marked  
Contact Manufacturer

### Certifications

CSA Certified  
UL Listed

### Catalog Notes

Complete Assembled Switches; Consult factory for CE approval status

## defaultTaxonomyAttributeLabel

### Contact Rating

10A at 600Vac, 0.22A at 125Vdc

### Enclosure material

Die cast zinc

### Connection

Screw terminal

### Contact configuration

1 NO-1 NC

### Switch type

Top rotary

### Operating temperature - max

200 °F

### Operating temperature - min

-20 °F

### Environmental rating

NEMA 1, NEMA 4, NEMA 13

### Maximum AC current

10 A

### Maximum DC current

0.22 A

## Resources

### Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

### Specifications and datasheets

[Eaton Specification Sheet - 10316H700](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)