Product specifications

Eaton 9PX11KPM



Catalog Number: 9PX11KPM

Eaton 9PX power module, Network card included, 3U, 11 kVA, 10 kW, Hardwired input, Outputs: Hardwired, 208V

General specifications

Product Name
Eaton 9PX power module

Catalog Number
9PX11KPM

UPC
743172039262

Product Length/Depth
27.56 in

Product Height
5.1 in

Product Width
17.3 in

Product Weight
62 lb

Warranty
3 year limited

Compliances
CE Marked
FCC Part 15
CISPR22 Class A / FCC part 15 Class A

Certifications
cULus Listed
IEC 62040-2:2006 Cat C2
NOM
ENERGY STAR certified

Catalog Notes
Add up to 5 extended battery modules (EBM) with UPS; add up to 12 EBMs with SC240RT supercharger module

Powering Business Worldwide

Battery

Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

Battery type

Sealed, lead-acid

Extended battery capability

Yes

Electrical output

Receptacle

Hardwired

Topology

Online/Double-conversion

Wattage

10 kW

VA rating

11 kVA

Output waveform

True sine wave

Voltage

208 V

Output power factor

0.91

Output nominal voltage

208V default (200/208/220/230/240/250V)

Output voltage range

±1% steady-state

Output frequency

50/60 Hz

Electrical input

Input connection

Hardwired

Input nominal voltage

208V default (200/208/220/230/240/250V)

Input frequency range

60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz

Input power factor

>0.99 typical

Communications

Communication

Web/SNMP in MiniSlot expansion port + 1 USB port + 1 serial RS232 port + 1 mini-terminal block for remote ON/OFF + 1 mini-terminal block for remote power off + 1 mini-terminal block for output relay Communication slot

Expansion slots

(1) Mini-Slot (MS) expansion port with Gigabit Network Card (NETWORK-M2) included

Ethernet interface

Yes

Includes network card

Yes

Software compatibility

Intelligent Power Software Suite

User interface

Graphical display, 5-button programmable menu

Environmental

Altitude

<1000m for nominal power, 10% power degrading every 1000m (up to 3000m)

BTU Rating

Online: 1920, Battery: 2900

Noise level

<45 dB at 1 meter

Relative humidity

0-95% non-condensing

Temperature range

0° to 40°C (32° to 104°F)

Additional specifications

Special features

Gigabit Network Card (NETWORK-M2) included

Form factor

Rack/tower

Rack size

3U

Rack mounting kit

Yes

Efficiency

94%

Package contents

9PX11KPM 11 kVA 3U UPS
power module
Gigabit Network Card
(NETWORK-M2)
4-post rail kit
User manual
Quick start guide
Tower pedestals
Intelligent Power Software
Suite CD
RS-232 serial cable
USB cable
Cable gland for hardwire

Warranty and support

Standard factory warranty

3-YEAR FACTORY
WARRANTY
- 3 years
- Parts, electronics and
batteries coverage
- Standard ground shipping
- Technical support

Extended service plans

ADVANCED DEPOT
EXCHANGE
- 5-year depot repair:
9SW5Y-11000UC
- Expedited parts coverage
for 5 years
- Parts, electronics and UPS
batteries coverage
- Next business day
shipping
- Technical support
5-YEAR ON-SITE PLAN:
WFLN75XX-11000UC
- On-site parts and labor
coverage for years 5
- Parts, electronics and UPS
batteries coverage

connection

Phillips head screw driver

Internal bypass

Yes

- 24x7 on-site labor coverage, next-day response
- Next-day shipping
- Technical support

Resources

Brochures

Eaton 9PX 5-11 kVA UPS brochure

Manuals and user guides

Eaton Bypass Power Module (BPM) user guide

Specifications and datasheets

Product Data Sheet - 9PX11KPM

Eaton Specification Sheet - 9PX11KPM

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia