

Eaton C25KNE3300AC

Catalog Number: C25KNE3300AC

Eaton definite purpose contactor, Non-reversing contactors and starters (C306) , 200 and 300A, three-pole , Open with metal mounting plate, Box lugs (posidrive setscrew) ,3P, 300A, 110–120 Vac, 50/60 Hz , 1NO-1NC pressure plate



General specifications

Product Name	Catalog Number
Eaton definite purpose contactor	C25KNE3300AC
UPC	Product Length/Depth
782114181508	7.25 in
Product Height	Product Width
9.11 in	7.05 in
Product Weight	Warranty
20 lb	1 year
Compliances	Certifications
RoHS Compliant	CSA Certified UL Recognized

Catalog Notes

Resistive Load rating per pole. Auxiliary contact includes standard pressure plate terminals.

defaultTaxonomyAttributeLabel

Amperage Rating

360A

Number Of Poles

Three-pole

Type

Non-reversing

Coil

110-120 Vac, 50/60 Hz

Contact configuration

1 NO, 1 NC

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

300 A

Model

Contactors

Resistive load

360 A

Size

360A, three-pole

Terminals

Box lugs (posidrive setscrew)

Connection

Quick

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Specifications and datasheets

[Eaton Specification Sheet - C25KNE3300AC](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)