

Eaton C25DRF340B

Catalog Number: C25DRF340B

Eaton definite purpose contactor, Quick, 25A, 12 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 25A, Contactor, Four-pole, 35A, Screw/pressure plate and quick connect terminals (side-by-side), Non-reversing

General specifications



| | |
|----------------------------------|---|
| Product Name | Catalog Number |
| Eaton definite purpose contactor | C25DRF340B |
| UPC | Product Length/Depth |
| 782116483969 | 3.35 in |
| Product Height | Product Width |
| 3.75 in | 2.4 in |
| Product Weight | Warranty |
| 1.19 lb | 1 year |
| Compliances | Certifications |
| RoHS Compliant | UL Recognized CSA Certified UL Listed file E1491 (Guide Number NLDX2) |

defaultTaxonomyAttributeLabel

Amperage Rating

40A

Number Of Poles

Three-pole

Options

Global listed

Type

Non-reversing

Auxiliary contacts

Quick connect (side-by-side)

Coil

208-240 Vac, 50/60 Hz

Coil voltage

24 Vac, 50/60 Hz

Enclosure

Open with DIN rail mounting adapter

Frame size

15-50 A, two-pole and three-pole

Inductive full load

40 A

Model

Contactor

Resistive load

50 A

Series

D1

Terminals

Box lugs (posidrive setscrew)

Connection

Quick

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

C25DRF3 3D Model Xchange

C25DRF3 AutoCAD 2D Footprint

C25DRF3 2D PDF

C25DRF3 2D Drawing Xchange

C25DRF3 3D Inventor

C25DRF3 AutoCAD 2D Footprint (mm)

Specifications and datasheets

Eaton Specification Sheet - C25DRF340B



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)