Product specifications

Eaton C25END440T

Catalog Number: C25END440T

Eaton definite purpose contactor, Quick, 60A, 208-240 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 60A, Contactor, Two-pole, 75A, Box lugs (posidrive setscrew) and quick connect terminals , Non-reversing



General specifications

Product Name
Eaton definite purpose contactor

Catalog Number
C25END440T

UPC
782113608952

Product Length/Depth
3.38 in

Product Height
3.75 in

Product Width
2.68 in

Product Weight
2.19 lb

Warranty
1 year

Compliances
RoHS Compliant

Certifications
UL Recognized
CSA Certified

Catalog Notes
Resitive Load rating per pole

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Amperage Rating

40A

Number Of Poles

Four-pole

Type

Non-reversing

Coil

24 Vac, 50/60 Hz

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

40 A

Model

Contactor

Resistive load

50 A

Terminals

Box lugs (posidrive setscrew)

Connection

Quick

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Specifications and datasheets

Eaton Specification Sheet - C25END440T

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia