Product specifications

Eaton C25DND325C-GL

Catalog Number: C25DND325C-GL

Eaton definite purpose contactor, Mounting plate, Quick, Pressure plate quick connect (side-by-side), 440-480 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, Contactor, Three-pole, Global listed, Non-reversing



General specifications

Product Name
Eaton definite purpose contactor

Catalog Number
C25DND325C-GL

UPC
786685696041

Product Length/Depth
3.35 in

Product Height
3.75 in

Product Width
2.4 in

Product Weight
1.19 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances
RoHS Compliant
CE Marked

Certifications
CSA Certified
UL Listed file E1491 (Guide Number NLDX2)

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Accessories

Mounting plate

Number Of Poles

Three-pole

Options

Global listed

Type

Non-reversing

Auxiliary contacts

Pressure plate quick connect (side-by-side)

Coil voltage

440-480 Vac, 50/60 Hz

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Model

Contactor

Series

D1

Terminals

Screw

Connection

Quick

Resources

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

C25DND3 AutoCAD 2D Footprint (mm)

C25DND3 2D PDF

C25DND3 AutoCAD 2D Footprint

C25DND3 3D Inventor

C25DND3 2D Drawing Xchange

C25DND3 3D Model Xchange

Specifications and datasheets

Eaton Specification Sheet - C25DND325C-GL

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia