

Eaton DH362UDK-GCL

Catalog Number: DH362UDK-GCL

Eaton Custom single-throw non-fused safety switch, Mill-duty rated, 60 A, NEMA 12, Painted galvanized steel, Non-Fusible, Three-pole, Three-wire, 10 at 240 Vac TD 1 Ph, 20 at 480 Vac TD 1 Ph, 25 at 600 Vac TD 1 Ph, 50 at 480 Vac TD 3 Ph

General specifications



Photo is representative

Product Name

Eaton custom single-throw non-fused safety switch

Catalog Number

DH362UDK-GCL

UPC

782114889749

Product Length/Depth

10.22 in

Product Height

14.14 in

Product Width

8.76 in

Product Weight

28 lb

Warranty

Eaton Selling Policy 25-000, one (1) year UL Listed from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications

Catalog Notes

Suitable for service entrance use with a Neutral Kit installed. Can be field modified to meet NEMA 3R rainproof requirements when a factory provided drain hole is opened. Use outside poles of three-pole switch for two-pole applications.

defaultTaxonomyAttributeLabel

Special features

Mill-duty

Type

Mill-duty rated

Amperage Rating

60A

Number Of Poles

Three-pole

Product Category

Heavy Duty, Mill-duty

Voltage rating

600 V

HP rating - max

10 at 240 Vac TD 1 Ph, 20 at 480 Vac TD 1 Ph, 25 at 600 Vac TD 1 Ph, 50 at 480 Vac TD 3 Ph, 60 at 600 Vac TD 3 Ph, 10 at 250 Vdc

Enclosure

NEMA 12

Enclosure material

Painted galvanized steel

Fuse configuration

Non-fusible

Number of wires

3

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Specifications and datasheets

[Eaton Specification Sheet - DH362UDK-GCL](#)