Product specifications

Eaton ECC03C1A8A-L24



Catalog Number: ECC03C1A8A-L24

Eaton C30CN mechanically held lighting contactor, 30 A, 110 V/50 Hz, 120 V/60 Hz, 30 A, NEMA 1, Painted steel, Eight-pole, Electrically held, C30CN Series, 4 NC power pole, Non-combination electrically and mechanically held

General specifications

Product Name
Eaton C30CN mechanically held lighting contactor

Catalog Number
ECC03C1A8A-L24

UPC
786685358536

Product Length/Depth
7.62 in

Product Height
12.6 in

Product Width
6 in

Product Weight
11.5 lb

Warranty
1 year

Certifications
UL Listed
cUL Listed

Catalog Notes
Ampere rating is based on a maximum load voltage of 480V for tungsten lamp applications and 600V for ballast or mercury vapor type applications

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Accessories

Red RUN pilot light, HAND/OFF/AUTO selector switch

Amperage Rating

30A

Number Of Poles

Eight-pole

Special features

4 NC power pole

Type

Non-combination electrically and mechanically held

Coil voltage

110-120 Vac, 50/60 Hz

Contact rating

30 A

Enclosure

NEMA 1

Enclosure material

Painted steel

Operation

Electrically held

Series

C30CN

Resources

Brochures

Lighting contactors

Catalogs

Eaton's Volume 10—Enclosed Control

Specifications and datasheets

Eaton Specification Sheet - ECC03C1A8A-L24

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia