Product specifications

Eaton ECC03C2ABA-S3

Catalog Number: ECC03C2ABA-S3

Eaton C30CN mechanically held lighting contactor, HAND/OFF/AUTO selector switch, 30 A, 110 V/50 Hz, 120 V/60 Hz, 30 A, NEMA 3R, Painted steel, 12-pole, Electrically held, C30CN Series, Non-combination electrically and mechanically held

Photo is representative

General specifications

Product Name	**Catalog Number**
Eaton C30CN mechanically held lighting contactor	ECC03C2ABA-S3
	UPC
	782116163106
Product Length/Depth	**Product Height**
8.625 in	15.875 in
Product Width	**Product Weight**
8.375 in	20 lb
Warranty	**Certifications**
1 year	cUL Listed UL Listed

Catalog Notes

Ampere rating is based on a maximum load voltage of 480V for tungsten lamp applications and 600V for ballast or mercury vapor type applications

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Accessories

START/STOP pushbutton

Amperage Rating

30A

Number Of Poles

Two-pole

Type

Non-combination electrically and mechanically held

Coil voltage

277 Vac, 60 Hz

Contact rating

30 A

Enclosure

NEMA 3R

Enclosure material

Painted steel

Operation

Electrically held

Series

C30CN

Resources

Brochures

Lighting contactors

Catalogs

Eaton's Volume 10—Enclosed Control

Specifications and datasheets

Eaton Specification Sheet - ECC03C2ABA-S3

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Powering Business Worldwide

Eaton.com/socialmedia