

Eaton EMAT10-10

Catalog Number: EMAT10-10

Eaton Managed rack PDU, 1U, C20 input, 3.84 kW max, 200-240V, 16A, 10 ft cord, Single-phase, Outlets: (8) C13 Outlet grip

General specifications



Product Name	Catalog Number
Eaton Managed Rack PDU	EMAT10-10
UPC	Product Length/Depth
743172082671	19 in
Product Height	Product Width
8 in	1.69 in
Product Weight	Warranty
6 lb	3 year
Compliances	Certifications
Contact Manufacturer	UL Listed

defaultTaxonomyAttributeLabel

Type

ePDU

Form factor

1U

Outlet control

Yes

Accessories

Yes

Package contents

Yes

Operating Temperature

0° to 60°C (32° to 140°F)

Mounting direction

Horizontal

Color

Black

Input connection

C20

Cord length

10 ft

Wattage

3.84 kW max

Amperage Rating

16A

Input voltage

200-240V

Phase

Single-phase

Frequency rating

50-60 Hz

Outlets

(8) C13

Number of Outputs C13

8

Series

Resources

Catalogs

[Operating manual](#)

Certification reports

[Eaton ePDU certificate of volatility](#)

[Eaton RoHS Declaration of Conformity: ePDU G3](#)

Drawings

[Eaton Advanced Monitored and Managed ePDU visio stencil](#)

[Eaton ePDU Managed EMAT10-10 technical drawing](#)

Manuals and user guides

[Eaton ePDU G3 replace and configure eNMC module](#)

[Eaton Double-wide G3 ePDU installation and connectivity quick start guide](#)

[Eaton ePDU G3 operations manual](#)

[Eaton ePDU G3 1U and 2U installation addendum](#)

[Eaton ePDU G3 instruction set - system objects](#)

Specifications and datasheets

[Eaton Specification Sheet - EMAT10-10](#)

Managed



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)