Product specifications

Eaton EMAU05-10



Catalog Number: EMAU05-10

Eaton Managed rack PDU, 2U, L5-30P input, 2.88 kW max, 120V, 24A, 10 ft cord, Single-phase, Outlets: (16) 5-20R

General specifications

Product Name	**Catalog Number**
Eaton Managed Rack PDU	EMAU05-10
UPC	**Product Length/Depth**
743172082688	19 in
Product Height	**Product Width**
5 in	3.4 in
Product Weight	**Warranty**
13 lb	3 year
Compliances	**Certifications**
Contact Manufacturer	UL Listed

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

ePDU

Form factor

2U

Outlet control

Yes

Accessories

Yes

Package contents

Yes

Operating Temperature

0° to 60°C (32° to 140°F)

Mounting direction

Horizontal

Color

Black

Input connection

L5-30P

Cord length

10 ft

Wattage

2.88 kW max

Amperage Rating

24A

Input voltage

120V

Phase

Single-phase

Frequency rating

50-60 Hz

Outlets

(16) 5-20R

Number of Outputs 5-20R

16

Number of Outputs C13

Resources

Certification reports

Eaton ePDU certificate of volatility

Eaton RoHS Declaration of Conformity: ePDU G3

Drawings

Eaton Advanced Monitored and Managed ePDU visio stencil

Eaton ePDU Managed EMAU05-10 technical drawing

Manuals and user guides

Eaton ePDU G3 1U and 2U installation addendum

Eaton ePDU G3 instruction set - system objects

Eaton ePDU G3 operations manual

Eaton Double-wide G3 ePDU installation and connectivity quick start guide

Eaton ePDU G3 replace and configure eNMC module

Specifications and datasheets

Eaton Specification Sheet - EMAU05-10

12

Number of Outputs C19

4

Series

Managed

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia