Product specifications

Eaton HP404040SHFA

Catalog Number: HP404040SHFA

Eaton house panel, 400A, Aluminum, Manual bypass, NEMA 3R, Underground, 22 kAIC, Lug landings for compression, lugs not included, CSR2200, Semi-flush mounting, C:40, S:1, SP:40, BRH/BWH, Ring, Type BR breakers, 120/240V, 4306



Photo is representative

General specifications

Product Name
Eaton house panel

Catalog Number
HP404040SHFA

UPC
782116959976

Product Length/Depth
45 in

Product Height
7.5 in

Product Width
31 in

Product Weight
155 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances
EUSERC Approved

Certifications
UL Listed

Catalog Notes
Includes manual bypass and additional ground lug to meet Nevada requirements. Load conductors can exit the top, bottom, side or back. Secondary breaker not included.

Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

House panel

Interrupt rating

10 kAIC

Enclosure

NEMA 3R

Secondary circuit breaker

BRH/BWH

Amperage Rating

400 A

Line

Lug landings for compression, lugs not included

Mounting

Semi-flush

Number of spaces

40

Security

Ring

Voltage rating

120/240 V

Number of sockets

1

Used with

Type BR breakers

Bypass

Manual

Number of circuits

40

Bus material

Aluminum

Feed type

Bottom

Main circuit breaker

CSR2200

Resources

Catalogs

Eaton's Volume 1—Residential and Light Commercial

Drawings

Dimensional Drawing - METER BREAKER HP40SH and SHA, HP404040SH and SHA

Specifications and datasheets

Eaton Specification Sheet - HP404040SHFA



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia