

# Eaton KD2225

Catalog Number: KD2225

Eaton Series C complete molded case circuit breaker, K-frame, KD, Complete breaker, Fixed thermal, fixed magnetic trip, Two-pole, 225A, 600 Vac, 250 Vdc, 65 kAIC at 240 Vac, 35 kAIC at 480 Vac, Aluminum, Line and load, 50/60 Hz

## General specifications



Photo is representative

|                                                                                                                                                                                            |                       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| <b>Product Name</b>                                                                                                                                                                        | <b>Catalog Number</b> |
| Eaton Series C complete molded case circuit breaker                                                                                                                                        | KD2225                |
|                                                                                                                                                                                            | <b>UPC</b>            |
|                                                                                                                                                                                            | 786679349052          |
| <b>Product Length/Depth</b>                                                                                                                                                                | <b>Product Height</b> |
| 4.1 in                                                                                                                                                                                     | 5.5 in                |
| <b>Product Width</b>                                                                                                                                                                       | <b>Product Weight</b> |
| 5.5 in                                                                                                                                                                                     | 11.5 lb               |
| <b>Warranty</b>                                                                                                                                                                            | <b>Certifications</b> |
| Eaton Selling Policy 25-000, one (1) year UL Listed from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first. |                       |

## defaultTaxonomyAttributeLabel

### Amperage Rating

225 A

### Voltage rating

600 Vac, 250 Vdc

### Trip Type

Fixed thermal, fixed magnetic

### Circuit breaker type

KD

### Circuit breaker frame type

Complete breaker

### Series

Series C

### Terminals

Line and load

### Frame

K

### Frequency rating

50 to 60 Hz

### Terminal material

Aluminum

### Interrupt rating

65 kAIC at 240 Vac

35 kAIC at 480 Vac

### Number of poles

Two-pole

## Resources

### Application notes

[Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)

[UL listed 100%-rated molded case circuit breakers](#)

[Application of Tap Rules to Molded Case Breaker Terminals](#)

### Brochures

[Motor protection circuit breakers product aid](#)

[MOEM MCCB Product Selection Guide](#)

[StrandAble terminals product aid](#)

[Plug-in adapters for molded case circuit breakers product aid](#)

[Power metering and monitoring with Modbus RTU product aid](#)

[Current limiting Series C molded case circuit breakers product aid](#)

[Circuit breaker motor operators product aid](#)

[Multi-wire lugs product aid](#)

[Breaker service centers](#)

### Catalogs

[Molded case circuit breakers catalog](#)

[Eaton's Volume 4—Circuit Protection](#)

### Drawings

[KD2 3D Model Xchange](#)

[KD2 AutoCAD 2D Footprint](#)

[KD2 2D Drawing Xchange](#)

[KD2 3D Inventor](#)

[KD2 AutoCAD 2D Footprint \(mm\)](#)

[KD2 2D PDF](#)

### Installation instructions

[Instruction Leaflet for the KES 310+ Electronic Trip Unit](#)

[Installation Instructions for DK, KDB, KD, HKD, KDC, KW, HKW, KWC, CKD, CHKD Circuit Breakers and Molded Case Switches](#)

### Multimedia

[Circuit Breakers Explained](#)

[Circuit breakers explained](#)

### Specifications and datasheets

[Series C F-Frame molded case circuit breakers](#)

[Eaton Specification Sheet - KD2225](#)

[F-Frame 310+ Molded-case circuit breakers 15-225A](#)

[MOEM MCCB product selection guide](#)

Series C G-Frame molded case circuit breakers time current curves

Series C J-Frame molded case circuit breakers time current curves



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.  
All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)