Product specifications

Eaton MD75E79CU

Catalog Number: MD75E79CU

Drive Isolation Transformer, Ventilated, Dry Type Distribution, DT-3, Three-phase, PV: 480 delta, Taps: 1 at +5% FCAN, 1 at -5% FCBN, SV: 480Y/277, 150°C, 75 kVA, Cu windings, Frame: 916A, uses WS19



Photo is representative

General specifications

Product Name
Eaton Motor drive isolation ventilated transformer

Catalog Number
MD75E79CU

UPC
786685266985

Product Length/Depth
23.42 in

Product Height
48.56 in

Product Width
28.22 in

Product Weight
873 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications
UL Listed

Powering Business Worldwide

Physical Attributes

Coil material
Copper

Design
DT-3

Frame
916A

Tap size
1 at +5% FCAN, 1 at -5% FCBN

Type
Dry Type Distribution, Drive Isolation Transformer

Performance Ratings

Frequency rating
60 Hz

Phase
Three-phase

Primary voltage
480 V

Secondary Voltage
480Y/277 V

Temperature rise
150 °C rise

Volt ampere rating
75 kVA

Miscellaneous

Weathershield
WS19

Resources

Catalogs
Eaton's Volume 2—Commercial Distribution

Specifications and datasheets
Eaton Specification Sheet - MD75E79CU

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia