Product specifications

Eaton N48M28B30CUEE

Catalog Number: N48M28B30CUEE

Eaton K-Factor nonlinear ventilated transformer, KT-13 (3-phase), PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 208Y/120V, 80°C rise, 30 kVA, Copper windings, EE

Photo is representative

General specifications

Product Name
Eaton K-Factor nonlinear ventilated transformer

Catalog Number
N48M28B30CUEE

UPC
786680034572

Product Length/Depth
16.5 in

Product Height
30 in

Product Width
23 in

Product Weight
490 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances
NEMA TP-1 Compliant

Certifications
UL Listed

Catalog Notes
Nema TP-1 efficient

Powering Business Worldwide

Physical Attributes

Coil material

Copper

Frame

912B

Tap size

2 at +2.5% FCAN, 4 at -2.5% FCBN

Performance Ratings

Frequency rating

60 Hz

Volt ampere rating

30 kVA

Phase

Three-phase

Primary voltage

480 V

Secondary Voltage

208 Y/120 V

Temperature rise

80 °C rise

Miscellaneous

Special features

Electrostatically Shielded

Weathershield

WS38

Resources

Catalogs

Eaton's Volume 2—Commercial Distribution

Multimedia

Eaton's Transformer Flex Center

Specifications and datasheets

Eaton Specification Sheet - N48M28B30CUEE

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia