

Eaton N48M28F22CUEE

Catalog Number: N48M28F22CUEE

Eaton K-Factor nonlinear ventilated transformer, KT-13 (3-phase), PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 208Y/120V, 115°C rise, 225 kVA, Copper windings, EE



Photo is representative

General specifications

Product Name	Catalog Number
Eaton K-Factor nonlinear ventilated transformer	N48M28F22CUEE
	UPC
	786680034558
Product Length/Depth	Product Height
32.65 in	57.54 in
Product Width	Product Weight
36.69 in	2354 lb
Warranty	Compliances
Eaton Selling Policy 25-000, one (1) year NEMA TP-1 Compliant from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	Certifications
	UL Listed
	Catalog Notes
	Nema TP-1 efficient

Physical Attributes

Coil material

Copper

Frame

923

Tap size

2 at +2.5% FCAN, 4 at -2.5% FCBN

Performance Ratings

Frequency rating

60 Hz

Volt ampere rating

225 kVA

Phase

Three-phase

Primary voltage

480 V

Secondary Voltage

208 Y/120 V

Temperature rise

115 °C rise

Miscellaneous

Special features

Electrostatically Shielded

Weathershield

WS37

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Multimedia

[Eaton's Transformer Flex Center](#)

Specifications and datasheets

[Eaton Specification Sheet - N48M28F22CUEE](#)

Warranty guides

[Selling Policy 25-000 - Distribution and Control Products and Services](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)