

Eaton N48M28B33EE

Catalog Number: N48M28B33EE

Eaton K-Factor nonlinear ventilated transformer, KT-13 (3-phase), PV 480V, Taps: 2 at +2.5% /4 at -2.5%, SV 208Y/120V, 80°C rise, 300 kVA, EE



Photo is representative

General specifications

Product Name

Eaton K-Factor nonlinear ventilated transformer

Catalog Number

N48M28B33EE

UPC

786685223407

Product Length/Depth

36.23 in

Product Height

75 in

Product Width

44.2 in

Product Weight

3410 lb

Warranty

Eaton Selling Policy 25-000, one (1) year NEMA TP-1 Compliant from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances

Certifications

UL Listed

Catalog Notes

Nema TP-1 efficient

Physical Attributes

Coil material

Aluminum

Frame

920E

Tap size

2 at +2.5% FCAN, 4 at -2.5% FCBN

Performance Ratings

Frequency rating

60 Hz

Volt ampere rating

300 kVA

Phase

Three-phase

Primary voltage

480 V

Secondary Voltage

208 Y/120 V

Temperature rise

80 °C rise

Miscellaneous

Special features

Electrostatically Shielded

Weathershield

WS35

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Multimedia

[Eaton's Transformer Flex Center](#)

Specifications and datasheets

[Eaton Specification Sheet - N48M28B33EE](#)

Warranty guides

[Selling Policy 25-000 - Distribution and Control Products and Services](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)