Product specifications

Eaton T20P11S75

Catalog Number: T20P11S75

General-Purpose Transformer, Ventilated, Dry Type Distribution, DS-3, PV: 240 X 480V, Taps: 1 at +5% FCAN, 2 at -5% FCBN X 2 at +2.5% FCAN, 4 at -2.5% FCBN, SV: 120/240V, 150°C, 75 kVA , Al windings , Frame: 819, uses WS16, Single-phase



Photo is representative

General specifications

Product Name
Eaton General purpose ventilated transformer

Catalog Number
T20P11S75

UPC
786680021183

Product Length/Depth
23.84 in

Product Height
42.03 in

Product Width
24.22 in

Product Weight
265 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications
UL Listed

Catalog Notes
+1 - 5% , -2 - 5% at 240V primary, +2 - 2.5% , -4 - 2.5% at 480V primary

Powering Business Worldwide

Physical Attributes

Coil material

Aluminum

Design

DS-3

Frame

819

Tap size

1 at +5% FCAN, 2 at -5% FCBN x 2 at +2.5% FCAN, 4 at -2.5% FCBN

Type

Dry Type Distribution Transformer

Performance Ratings

Frequency rating

60 Hz

Kva Rating

75 kVA

Primary voltage

240 V, 480 V

Secondary Voltage

120/240 V

Temperature rise

150 °C rise

Miscellaneous

Weathershield

WS16

Resources

Catalogs

Eaton's Volume 2—Commercial Distribution

Specifications and datasheets

Eaton Specification Sheet - T20P11S75

Warranty guides

Selling Policy 25-000 - Distribution and Control Products and Services

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia