



1 in. Liquidtight Straight Connector, Insulated

By Raco
Catalog # 3514DC



*Representative Image

1 in. Liquidtight Straight Connector, Insulated

Features

- Diecast zinc construction
- Insulated
- cULus
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

General

| | |
|--------------------------|------------------------|
| Conduit Type | Flexible Metal Conduit |
| EU RoHS Indicator | Contact Manufacturer |
| Environmental Conditions | Wet Location |
| Fitting Type | Connectors |
| Insulation Type | Insulated |
| Material | Die Cast Zinc |
| UPC | 050169980217 |

Dimensions

| | |
|------------|--------------------------------|
| Dimensions | 1.951 in x 1.835 in x 1.945 in |
| Height | 1.945 in |
| Length | 1.951 in |
| Trade Size | 1 in |
| Weight | 0.308 lb |
| Width | 1.835 in |

Certifications And Compliance

| | |
|------------------|--------------|
| Certified Listed | cULus Listed |
|------------------|--------------|

Logistics

| | |
|-----------------------|------|
| Carton Quantity | 10 |
| Minimum Pack Quantity | 10 |
| Pallet Quantity | 7200 |

Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)
[Product Logo - LT COND](#)
[Sales Drawings - 3511DC](#)
[SDS - HCC_SDS](#)
[Sell Sheets - Die Cast LiquidTight Fittings](#)
[Terms and Conditions - HCC Terms & Conditions](#)
[Video - RACO: Liquidtight Connectors vs. popular competitor](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-3514DC-SPEC-EN | REV 5/2024