BURNDY

Compression Splice Reducer

By Burndy
Catalog # YSR8CFX14CLTCKITC



CU Splice Reducer, Barrel A 8 Flex G,H,I,K,M,DLO, 8 AWG, Barrel B 1410 AWG, Standard Barrel, Internal Chamfer, Tin Plated, Connector is UL/CSA, 90°C Up to 35kV, Kit comes with Clear Heat Shrink, Red Color Code, 49 Die Index.

Application

Wire Reducing Splice

General

Catalog Number	YSR8CFX14CLTCKITC
Color Code	Red, Gray
Color Code - Side A	Red
Connector Type	STANDARD BARREL KITS
Construction Material - Main	Copper
Die Index	49
Die Index - Element A	49
Die Index Run Side	49
EU RoHS Indicator	Contact Manufacturer
Feature - Barrel Style	Skived
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Temperature Rating	194
Trade Name	HYREDUCER™
Type	YSR-TC
UPC	781810473986
UPC 12 Digit	7818104739866

Dimensions

Dimension - B Length fraction	9/16 in
Dimension - B Length inch	0.57 in
Dimension - L Length Overall mm	36 mm
Dimension - Length BB inch	0.66 in
Dimension - Length Overall inch	1.41 in
Dimension - Strip Length inch	0.57 in

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - Copper DLO Size Range	8 AWG
Conductor - Copper Flex G Run	8 AWG
Conductor - Copper Flex G Size A	8 AWG
Conductor - Copper Flex I Size A Range	8 AWG
Conductor - Copper Flex I Size B	10 AWG
Conductor - Copper Flex I Size B Range	10 AWG
Conductor - Copper Flex I Size Range	8 AWG
Conductor - Copper Flex K Run	8 AWG
Conductor - Copper Flex K Size A	8 AWG
Conductor - Copper Flex K Size A Range	8 AWG
Conductor - Copper Flex K Size B	10 AWG
Conductor - Copper Flex K Size B Range	10 AWG
Conductor - Copper Flex K Size Range	8 AWG
Conductor - Copper Flex M Run	8 AWG
Conductor - Copper Flex M Size A	8 AWG
Conductor - Copper Flex M Size A Range	8 AWG
Conductor - Copper Flex M Size B	10 AWG
Conductor - Copper Flex M Size B Range	10 AWG
Conductor - Copper Solid Size A	6
Conductor - Copper Solid Size B	12;11;10
Conductor - Copper Str Run Range	8 AWG
Conductor - Copper Str Size	8 AWG-14 AWG
Conductor - Copper Str Size B	10 AWG
Conductor - Copper Str Tap Range	14-10 AWG
Conductor - Material	COPPER
Conductor Size	8 AWG-14 AWG
Conductor Type	CODE/FLEX
Wire Size	8 AWG-14 AWG

Certifications And Compliance

Certification - CSA Approved	Yes

Size A	
Conductor - Copper Flex G Size A Range	8 AWG
Conductor - Copper Flex G Size B	10 AWG
Conductor - Copper Flex G Size B Range	10 AWG
Conductor - Copper Flex G Size Range	8 AWG
Conductor - Copper Flex H Run	8 AWG
Conductor - Copper Flex H Size A	8 AWG
Conductor - Copper Flex H Size A Range	8 AWG
Conductor - Copper Flex H Size B	10 AWG
Conductor - Copper Flex H Size B Range	10 AWG
Conductor - Copper Flex H Size Range	8 AWG
Conductor - Copper Flex I Run	8 AWG
Conductor - Copper Flex I	8 AWG

Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Carton Quantity	25
Pallet Quantity	6000

Product Assets

3D Models - YSR8CFX14CLTCKITC_MODEL-IGES
3D Models - YSR8CFX14CLTCKITC_MODEL-PDF
3D Models - YSR8CFX14CLTCKITC_MODEL-STEP
Catalogs - Full Line BURNDY Catalog
Catalogs - Section C - Compression Connections
Customer Notices - Prop 65 Notice
Installation Manuals - SPLICE KIT trilingual
Sales Drawings - 10021428

©2024 Hubbell Incorporated. All rights reserved.