



Materials & Finishes - Standard:

- **Base Metal:** Steel conforms to ASTM A1011 SS GR 33, A1011 HSLAS GR 45, A36, A575, A576, or A635.
- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC1
- **Power-Strut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A123 or A153
- **Perma-Green (GR):** Conforms to commercial standards for powder coating
- **Perma-Gold (ZD):** Conforms to ASTM B633, Type II SC1
- **Plain (PL):** No finish

Materials & Finishes - Special Metals:

- **Stainless Steel, Type 304 (SS):** Conforms to ASTM A240 or A276, Type 304 *
- **Stainless Steel, Type 316 (ST):** Conforms to ASTM A240 or A276, Type 316 *
- **Aluminum (AL):** Conforms to ASTM B209, Type 1100F or 5052-H32 *

* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

| Part No. | A | B | Finish | Product Weight / Piece (lbs) |
|----------|---------------|----------|--------|------------------------------|
| PS2404 | 2-3/8" (60) | 6"(152) | HG | 1.198 |
| PS2404 | 2-3/8" (60) | 6"(152) | GR | 1.13 |
| PS2405 | 4-3/8" (111) | 8" (203) | HG | 1.738 |
| PS2405 | 4-3/8" (111) | 8" (203) | GR | 1.64 |
| PS2406 | 6-3/8" (162) | 10 (254) | HG | 2.29 |
| PS2406 | 6-3/8" (162) | 10 (254) | GR | 2.16 |
| PS2407 | 8-3/8" (213) | 12 (305) | HG | 2.83 |
| PS2407 | 8-3/8" (213) | 12 (305) | GR | 2.67 |
| PS2408 | 10-3/8" (264) | 14 (356) | HG | 3.371 |
| PS2408 | 10-3/8" (264) | 14 (356) | GR | 3.18 |

| | | | |
|------------------------------|---|---------------|--|
| Project: | <input style="width: 100%;" type="text"/> | | |
| Architect / Engineer: | <input style="width: 100%;" type="text"/> | | |
| Date: | <input style="width: 25%;" type="text"/> | Phone: | <input style="width: 50%;" type="text"/> |
| Contractor: | <input style="width: 100%;" type="text"/> | | |
| Address: | <input style="width: 100%;" type="text"/> | | |
| Notes: | <input style="width: 100%;" type="text"/> | | |

Approval Stamp: