

PVC COATED GUA JUNCTION BOXES FOR HAZARDOUS LOCATIONS - GUAC

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior Urethane coating thickness is a minimum 0.002"
- Sizes available are ½" to 2"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes ½" - 2"

Applications:

Allied Tube & Conduit® GUA Style Fittings are available in a variety of shapes and dimensions. GUA style boxes are used in hazardous locations. All GUA style boxes are supplied PVC coated with PVC coated covers and a seal between the coating of the boxes and the coating of the covers.



Standards:

- National Electric Code:
Class I, Division 1 & 2, Groups C, D, Class III
- UL Standard 886
- ANSI Standard C-33.27
- CSA Standard: C22.2 No. 30
- NEMA/EEMAC 3, 4

Part Number	Trade Size (in)	Cover Opening (in)	A (in)	B (in)	C (in)	D (in)	Weight per 100 (lbs)
PV0500GUAC14	½	2	2.58	2.29	2.19	0.67	350
PV0500GUAC16	½	3	3.58	2.04	1.88	0.67	200
PV0700GUAC24	¾	2	2.58	2.04	2.00	0.79	350
PV0700GUAC26	¾	3	3.58	2.04	1.88	0.79	200
PV1000GUAC36	1	3	3.58	2.35	2.19	0.92	390
PV1200GUAC47	1¼	3½	4.33	2.73	2.75	1.13	520
PV1200GUAC49	1¼	5	5.83	3.85	3.75	1.32	950
PV1500GUAC59	1½	5	5.83	3.85	3.75	1.32	1100
PV2000GUAC69	2	5	5.83	4.10	4.00	1.60	1100

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit alliedeg.us