

PVC COATED CONDUIT HUBS - ST

Features:


- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- ST available in 12 trade sizes from ½" through 6"
- Sealing sleeves on conduit side of hub
- Sizes available are ½" to 2"
- For sizes 2½" - 6", the length of the sleeve extension(s) shall be at least 2"

Applications:

Allied Tube & Conduit® PVC Conduit Hubs are used to terminate conduit runs into electrical enclosures. Conduit hubs are available with or without grounding lug. PVC coating and internal urethane coating provide for superior corrosion protection. Electrical continuity is maintained across assembled joints.

Standards:

- UL Listed File #E308159
- NEC/CEC:
 - Class I, Division 2,
 - Class II, Division 1 & 2
 - Class III, Division 1 & 2
 - Class I, Zone 1, AEx e II
 - Class I, Zone 1, Ex e II
- All Screw-tight Hubs are manufactured in accordance with NEMA type enclosures 2, 3, 3R, 4, 4x, 11 and 12



Part Number	Trade Size (in)	A (in)	B (in)	C (in)	Max Wall Thickness (in)	Weight Per 100 (lbs)
PV0500ST1	½	1.84	2.00	1.31	0.125	20
PV0700ST2	¾	2.22	2.25	1.66	0.125	30
PV1000ST3	1	2.66	2.50	2.03	0.125	40
PV1200ST4	1¼	2.94	3.25	2.28	0.125	40
PV1500ST5	1½	3.19	3.50	2.53	0.125	60
PV2000ST6	2	3.75	4.25	3.09	0.125	120
PV2500ST7	2½	4.22	4.75	3.28	0.125	150
PV3000ST8	3	4.31	5.25	3.38	0.125	210
PV3500ST9	3½	4.38	5.50	3.44	0.125	300
PV4000ST10	4	4.44	6.25	3.50	0.125	350
PV5000ST11	5	4.94	7.50	4.00	0.125	540
PV6000ST12	6	5.00	8.50	4.00	0.125	690

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit alliedeg.us