

PVC COATED LIQUIDTIGHT CONNECTORS- STRAIGHT

Features:


- Exterior PVC coating thickness is a minimum 0.040"
- Sizes available are ½" to 4"
- The length of the sleeve extension(s) shall be at least equivalent to the nominal conduit size for sizes ½" - 2"
- For sizes 2½" - 4", the length of the sleeve extension(s) shall be at least 2"
- Available in straight, 45 degree or 90 degree body configurations

Applications:

Allied Tube & Conduit® PVC Coated Liquidtight Connectors are used with Liquidtight Conduit. The sleeve on the liquidtight connector is sized specifically to tighten around PVC conduit. Pulling compound is recommended for ease of installation. Fittings are provided with a flexible sleeve on the conduit side and a sealing form on both the box side and the mating part of the gland.

Standards:

- UL Standard 514B
- CSA Standard: C22.2 No. 18



Straight

Part Number	Trade Size (in)	A (in)	B (in)	C (in)	Weight per 100 (lbs)
PV0300LT38	⅜	1.24	1.88	0.56	20
PV0500LT50	½	1.46	2.06	0.56	20
PV0700LT75	¾	1.74	2.38	0.56	30
PV1000LT100	1	1.96	3.06	0.75	40
PV1200LT125	1¼	2.36	3.75	0.81	80
PV1500LT150	1½	2.80	4.19	0.81	90
PV2000LT200	2	3.33	5.06	0.88	170
PV2500LT250	2½	3.83	6.13	1.00	300
PV3000LT300	3	4.58	6.25	1.00	420
PV4000LT400	4	5.58	6.50	1.13	620

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit alliedeg.us