

PVC COATED DEVICE BOXES - FD

Features:

- Exterior PVC coating thickness is a minimum 0.040"
- Interior urethane coating thickness is a minimum 0.002"
- Sizes available are $\frac{1}{2}$ " to 1"
- Sealing sleeves on all conduit openings
- Modified boxes are available upon request
- All available covers are supplied with PVC coating

Applications:

Calbond Type FD PVC Coated Device Boxes offer corrosion protection to conduitsystems and accommodates wiring devices and access for taps and splices. Covers are available separately. Electrical continuity of the conduit system is maintained across assembled system.

Standards:

- UL Listed Standard 514B File #E307133
- CSA Standard: C22.2 No. 18



Part Number	Trade Size (in)	Weight per 100 (lbs)	A (in)	B (in)	C (in)	D (in)	Aluminum Item Number
Single Gang							
PV0500FD1	$\frac{1}{2}$	2.70	1.380	1.920	2.690	0.670	PA0500FD1SA
PV0700FD2	$\frac{3}{4}$	2.80	1.630	1.920	2.690	0.790	PA0700FD2SA
PV1000FD3	1	3.10	2.000	1.920	2.690	0.920	PA1000FD3SA

All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit calbond.com

