

Eaton SPD200208Y2C

Catalog Number: SPD200208Y2C

Surge Protection Device, SPD series, For switchboard, busways and panel boards (PRL1a, 2a, 3a, 3E, 4), 200 kAIC, 120/208V wye (4W+G), Standard feature package, Internal integrated mount, 150 L-N, 150 L-G, 150 N-G, 300 L-L operating voltage

General specifications



Product Name

Eaton SPD series surge protection device

Catalog Number

SPD200208Y2C

UPC

786685322766

Product Length/Depth

9.5 in

Product Height

3.45 in

Product Width

5.4 in

Product Weight

3.5 lb

Warranty

15 year

Certifications

UL 1449

UL Listed

Product specifications

Type

SPD

Special features

Meets or exceeds the requirements specified in IBC @2006, CBC2007, and UBC@Zone 4. Audible alarm with silence button. Form C relay contact. EMI/RFI filtering, providing up to 50 dB of noise attenuation from 10 kHz to 100 MHz. Surge counter with rest button

Accessories

Standard feature package

Frequency rating

50/60 Hz

Interrupt rating

200 kAIC

Nominal Discharge Current

20 kA

Operating voltage

150 L-N, 150 L-G, 150 N-G, 300 L-L

Used with

Switchboard, busways and panelboards (PRL1a, 2a, 3a, 3e, 4)

Voltage rating

120/208 wye (4W+G)

Surge current

200 kA per phase

Short-circuit rating

200 kA

Operating temperature

-40 to 50 °C

Mounting Method

Internal integrated

Resources

Brochures

[Eaton's SPD Series \(Integrated Versions\) Product Aid](#)

Installation instructions

[Eaton SPD Series - Surge Protective Device For Integrated Units](#)

Specifications and datasheets

[Eaton Specification Sheet - SPD200208Y2C](#)

[Eaton's SPD Series \(Integrated Versions\) Data Sheet](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia