BURNDY

Compression Splice Reducer

By Burndy
Catalog # YSR3434FXLTCKITC



CU Splice Reducer, Barrel A 500 kcmil, Barrel B 350 kcmil G,H,I,K,M,373 DLO, Standard Barrel, Internal Chamfer, Tin Plated, Connector is UL/CSA, 90°C Up to 35kV, Kit comes with Clear Heat Shrink, Brown/Blue Color Code, 20/19 or L80 Die Index.

Application

Wire Reducing Splice

General

Catalog Number	YSR3434FXLTCKITC
Color Code	Brown, Blue
Color Code - Side A	Brown
Color Code - Side B	Blue
Connector Type	STANDARD BARREL KITS
Die Index	20/19
Die Index - Element A	20
Die Index - Element B	19;L80
Die Index Run Side	20
Die Index Tap Side	19;L80
Feature - Barrel Style	Skived
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Temperature Rating	194
Trade Name	HYREDUCER™
UPC	781810472347
UPC 12 Digit	7818104723477

Dimensions

Dimension - B Length fraction	1-11/16 in
Dimension - B Length inch	1.69 in
Dimension - L Length Overall mm	89 mm
Dimension - Length BB inch	1.69 in
Dimension - Length Overall inch	3.51 in
Dimension - Strip Length inch	1.60 in

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - Copper Flex G Size B	350 kcmil
Conductor - Copper Flex G Size B Range	350 kcmil
Conductor - Copper Flex G Tap	350 KCMIL
Conductor - Copper Flex H Size B	350 kcmil
Conductor - Copper Flex H Size B Range	350 kcmil
Conductor - Copper Flex H Tap	350 KCMIL
Conductor - Copper Flex I Size B	350 kcmil
Conductor - Copper Flex I Size B Range	350 kcmil
Conductor - Copper Flex I Tap	350 KCMIL
Conductor - Copper Flex K Size B	350 kcmil
Conductor - Copper Flex K Size B Range	350 kcmil
Conductor - Copper Flex K Tap	350 KCMIL
Conductor - Copper Flex M Size B	350 kcmil
Conductor - Copper Flex M Size B Range	350 kcmil
Conductor - Copper Flex M Tap	350 KCMIL
Conductor - Copper Str Size	500 KCMIL-350 KCMIL
Conductor - Copper Str Size A	500 kcmil
Conductor - Copper Str Size A Range	500 kcmil
Conductor - Copper Str Size B	350 kcmil
Conductor - Material	COPPER
Conductor Size	500 KCMIL-350 KCMIL
Conductor Type	FLEX
Wire Size	500 KCMIL-350 KCMIL

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM

UL Listed	No

Logistics

Carton Quantity	20
Pallet Quantity	1800

Product Assets

3D Models - YSR3434FXLTCKITC_MODEL-STEP
3D Models - YSR3434FXLTCKITC_MODEL-PDF
3D Models - YSR3434FXLTCKITC_MODEL-IGES
Catalogs - Full Line BURNDY Catalog
Catalogs - Section C - Compression Connections
Customer Notices - Prop 65 Notice
Installation Manuals - SPLICE KIT trilingual
Sales Drawings - 10021428

©2024 Hubbell Incorporated. All rights reserved.