Compression Splice

By Burndy
Catalog # YSV4CFX

4 Flex G,H,I,K,M,DLO, 4 AWG AWG CU, Long Barrel, Internal Chamfer, Tin Plated, UL/CSA, 90°C, Up to 35kV, Gray Color Code, 8 Die Index.



Application

Wire Splice

General

Catalog Number	YSV4CFX
Color Code	Gray
Connector Type	LONG BARREL
Construction Material - Main	Copper
Die Index	8
EU RoHS Indicator	Contact Manufacturer
Finish Type	Tin-Plated
Material	COPPER
Trade Name	HYLINK™
Type	YSV
UPC	621945624047

Dimensions

Dimension - B Length inch	1.21
Length	2.79 in

Electrical Ratings

Voltage Rating	35 kV

Conductor Related

Conductor - Copper DLO Size	4 AWG
Conductor - Copper DLO Size Range	4 AWG
Conductor - Copper Flex G Size	4 AWG
Conductor - Copper Flex G Size Range	4 AWG
Conductor - Copper Flex H Size	4 AWG
Conductor - Copper Flex H Size Range	4 AWG
Conductor - Copper Flex I Size	4 AWG
Conductor - Copper Flex I Size Range	4 AWG
Conductor - Copper Flex K Size	4 AWG
Conductor - Copper Flex K Size Range	4 AWG
Conductor - Copper Flex M Size	4 AWG
Conductor - Copper Str Size	4 AWG
Conductor - Material	COPPER
Conductor Size	4 AWG
Conductor Type	CODE/FLEX
Wire Size	4 AWG

Certifications And Compliance

Certification - CSA Approved	CSA
Certification - cULus	NO
Industry Standard(s)	UL 486A-486B

Logistics

Carton Quantity	25

Product Assets

Brochures - Burndy_Copper Flex Splices - Long Barrel_Brochure
Catalogs - Full Line BURNDY Catalog
Catalogs - Section C - Compression Connections
Sales Drawings - 50117138

©2024 Hubbell Incorporated. All rights reserved.