

Eaton ABC-V-4-R

Catalog Number: ABC-V-4-R

Eaton GBB Series Very fast-acting fuse, 15A, 250 Vac, 125 Vdc



General specifications

Product Name	Catalog Number
Eaton Bussmann series ABC fast-acting fuse	ABC-V-4-R
	UPC
	051712646024
Product Length/Depth	Product Height
1.25 in	0.25 in
Product Width	Product Weight
0.25 in	0.008 lb
Compliances	Catalog Notes
RoHS Compliant CE Marked	Ceramic body allows for higher amp/volt rating combinations.

Product specifications

Used with

Axial leads- copper tinned wire

Type

Electronic

Application

Electronic circuits

Amperage Rating

4 A

Melting (I²T)

Typical pre-arc: 22.28

Resistance

0.031 ohms DC cold

Voltage drop

0.17 mV typical

Interrupt rating

10 kAIC at 125 Vac/dc

200 AIC at 250 Vac

Fuse indicator

Non-indicating

Connection

Ferrule end x ferrule end

Response time

4 hr at 100%, 60 min at 135%, 120 sec at 200%

Material

Nickel-plated brass endcaps

Ceramic tube

Quantity

4

Voltage rating

250 Vac, 125 Vdc, 32 Vac (self certified)

Resources

Specifications and datasheets

[Eaton ABC fast-acting ceramic tube fuses data sheet](#)

[Eaton Specification Sheet - ABC-V-4-R](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)