

Eaton ABC-2-R

Catalog Number: ABC-2-R

Eaton GBB Series Very fast-acting fuse, 25A, 250 Vac, 125 Vdc, R



General specifications

Product Name	Catalog Number
Eaton Bussmann series ABC fast-acting fuse	ABC-2-R
	UPC
	051712646208
Product Height	Product Diameter
32 mm	6 mm
Product Weight	Compliances
2.3 g	CE Marked
	RoHS Compliant

Catalog Notes

Ceramic body allows for higher amp/volt rating combinations.

Product specifications

Type

Electronic

Application

Electronic circuits

Amperage Rating

2 A

Melting (I²T)

Typical pre-arc: 2.167

Resistance

0.089 ohms DC cold

Voltage drop

0.31 mV typical

Interrupt rating

100 AIC at 250 Vac

10 kAIC at 125 Vac/dc

Fuse indicator

Non-indicating

Connection

Ferrule end x ferrule end

Response time

4 hr at 100%, 60 min at 135%, 120 sec at 200%

Material

Ceramic tube

Nickel-plated brass endcaps

Quantity

5

Voltage rating

250 Vac, 125 Vdc, 32 Vac (self certified)

Resources

PEP Eco-passport

[EATO-00033-V01.01-EN](#)

Specifications and datasheets

[Eaton ABC fast-acting ceramic tube fuses data sheet](#)

[Eaton Specification Sheet - ABC-2-R](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)