WSNLED and WNLED

Premium and utility commercial LED wraparound

Metalux

COOPER Lighting Solutions

WNLED/WSNLED Commercial LED wraparounds

These two product lines offer traditionally styled wraparound with Cooper Lighting Solutions' latest market leading LED and energy efficiency driver technologies. Offered in multiple lumen packages, color temperatures and driver options, the **WSNLED** and **WNLED** series enables customers to have the ideal balance with aesthetics, performance and energy efficiency. Additionally, the WSNLED series utilizes premium optical material which enhances the visual aesthetics providing customers with even, clean illumination eliminating lamp image commonly associated with traditional fluorescent solutions.

CELEBRATING 50+ YEARS

Performance

- 4 ft. and 2 ft. product configurations
- Lumen package - WSNLED (15) and WNLED (4)
- Evenly illuminated lens (WSNLED) for premium aesthetic or frost prismatic lens (WNLED)
- Multiple CCT: 3000K, 3500K, 4000K, 5000K at 82+ CRI
- Excellent performance, up to 118 lm/W
- Powered by Fifth Light. 0-10V dimming driver is standard
- Ideal for surface and suspended
- Suitable for use in clothes closets
- L88 at 60,000 hours
- Five-year warranty

Controls

- WNLED and WSNLED luminaires include 0-10V dimming drivers for control using wall dimmers (10% - 100%), daylighting sensors and room controllers from Cooper Lighting Solutions. Optional 1% dimming available.
- WNLED and WSNLED luminaires are available with native DALI drivers for complete digital energy management using Fifth Light addressable controls.

powered by fifthlight technology

Compliance

- LED modules comply with IESNA LM-79 and LM-80 standards
- cULus listed 1598 for damp locations
- RoHS compliant

Compliance and approvals

c UL us LISTED · DLC · RoHS COMPLIANT · LM79 / LM80 Compliant · Efficiency Standards T24 Can be used to comply with California Title 24 Non-Residential · damp location · 5 YEAR · Lasts 25 Years

Energy and performance

WNLED Utility LED wraparound					
Lumen type	**Length**	**Catalog number**	**Nominal 3500K lumens**	**Wattage**	**lm/W**
Standard	2 ft.	2WNLED-LD4-28SL-F-UNV-L835-CD1-U	2786	27.5	101
Standard	4 ft.	4WNLED-LD4-32SL-F-UNV-L835-CD1-U	3298	28.0	118
Standard	4 ft.	4WNLED-LD4-40SL-F-UNV-L835-CD1-U	4062	36.0	113
Standard	4 ft.	4WNLED-LD4-50SL-F-UNV-L835-CD1-U	4966	46.6	107

WSNLED Premium LED wraparound					
Lumen type	**Length**	**Catalog number**	**Nominal 3500K lumens**	**Wattage**	**lm/W**
Standard	2 ft.	2WSNLED-LD4-20SL-F-UNV-L835-CD1-U	2073	21.7	95
Standard	2 ft.	2WSNLED-LD4-24SL-F-UNV-L835-CD1-U	2390	25.6	93
Standard	2 ft.	2WSNLED-LD4-28SL-F-UNV-L835-CD1-U	2832	31.4	90
Standard	4 ft.	4WSNLED-LD4-20SL-F-UNV-L835-CD1-U	2009	18.3	110
Standard	4 ft.	4WSNLED-LD4-24SL-F-UNV-L835-CD1-U	2393	21.9	109
Standard	4 ft.	4WSNLED-LD4-28SL-F-UNV-L835-CD1-U	2853	26.5	108
Standard	4 ft.	4WSNLED-LD4-32SL-F-UNV-L835-CD1-U	3212	30.0	107
Standard	4 ft.	4WSNLED-LD4-36SL-F-UNV-L835-CD1-U	3653	34.8	105
Standard	4 ft.	4WSNLED-LD4-40SL-F-UNV-L835-CD1-U	4087	39.8	103
Standard	4 ft.	4WSNLED-LD4-44SL-F-UNV-L835-CD1-U	4424	43.8	101
High	4 ft.	4WSNLED-LD4-48HL-F-UNV-L835-CD1-U	4749	47.9	99
High	4 ft.	4WSNLED-LD4-52HL-F-UNV-L835-CD1-U	5138	53.3	96
High	4 ft.	4WSNLED-LD4-56HL-F-UNV-L835-CD1-U	5536	58.8	94
High	4 ft.	4WSNLED-LD4-60HL-F-UNV-L835-CD1-U	6064	66.9	91
High	4 ft.	4WSNLED-LD4-64HL-F-UNV-L835-CD1-U	6490	72.9	89

Lighting Brands
Ametrix
AtLite
Corelite
Ephesus
Fail-Safe
Halo
Halo Commercial
Invue
io
Iris
Lumark
Lumière
McGraw-Edison
Metalux
MWS
Neo-Ray
Portfolio
RSA
Shaper
Streetworks
Sure-Lites

Controls Brands
Greengate
Fifth Light

Connected Lighting Systems
HALO Home
WaveLinx

IoT Platform
Trellix

COOPER
Lighting Solutions

Cooper Lighting Solutions
1121 Highway 74 South
Peachtree City, GA 30269
P: 770-486-4800
www.cooperlighting.com

Canada Sales
5925 McLaughlin Road
Mississauga, Ontario L5R 1B8
P: 905-501-3000
F: 905-501-3172

Cooper Lighting Solutions is a registered trademark.

All other trademarks are property of their respective owners.

Product availability, specifications, and compliances are subject to change without notice.

© 2020 Cooper Lighting Solutions
All Rights Reserved
Printed in USA
Publication No. BR519017EN
January 27, 2021 10:17 AM