HSC100FR, Heat Shrink Tubing, 1" ID Min.(Exp.), 0.5" ID Max.(Rec.), 1/0-4/0 Flex, PVC, Flame Retardant, Clear, 600V.



By Burndy
Catalog # HSC100FR

Heat Shrink Tubing, 1" ID Min.(Exp.), 0.5" ID Max.(Rec.), 1/0-4/0 Flex, PVC, Flame Retardant, Clear, 600V.

General

Application	Used on UL Recognized TO 600V
Catalog Number	HSC100FR
Color	
Connector Type	CLEAR TUBES
EU RoHS Indicator	Yes
Material	Polyvinyl chloride
Sub Brand	VISISHRINK
Trade Name	VISI-SHRINK™
Type	HSC-FR, Fire Retardant
UPC	781810266120

Conductor Related

Conductor Range	#1/0 AWG to #4/0 AWG
Conductor Size	4/0AWG - 300kcmil

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Product Assets

Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Catalogs - BURNDY Master Catalog - Section D - Shrink Tubing
Interactive Catalog - BURNDY Full-Line Digital Catalog
Literature - Polyolefin Thin Wall Heat Shrink Cross Reference Guide
Product Cross Section Image(s) - BUR_HSC100FR_LineArt
Sales Drawings - 50015598

©2024 Hubbell Incorporated. All rights reserved